



EnergyVue Vinyl Non-Impact Windows and Doors

PRODUCT QUICK REFERENCE GUIDE

| PRODUCT STYLES AND SIZES | | | | | FRAME STYLES | | | | FRAME COLORS | TEST METHODS AND CERTIFICATIONS | | | | | | | |
|--------------------------|---------------|---------------------|--------------------------------------|---|-------------------------|-------------------|-----------|-----------|----------------------------|---------------------------------|-------------------|---------------------|------------------------|--------------------------|--------------|---|---|
| PRODUCT STYLE | CONFIGURATION | NOMINAL FRAME DEPTH | MINIMUM SIZE (ACTUAL DLO FRAME SIZE) | MAXIMUM SIZE (ACTUAL DLO FRAME SIZE) | 5/8" FLANGE | INTEGRAL NAIL FIN | J-CHANNEL | EQUAL LEG | WHITE, BEIGE BRONZE, BLACK | AAMA A440 | | TAS 201 / 202 / 203 | | FLORIDA PRODUCT APPROVAL | ENERGY STAR® | | |
| | | | | | | | | | | DESIGN PRESSURE* | KEY CERTIFICATION | DESIGN PRESSURE* | MIAMI-DADE NOA | | | | |
| SINGLE HUNG | (SH5400) | O/X Equal | 3-1/2" | 16-1/4" x 23-1/2" | 52-1/8" x 84" | ■ | ■ | ■ | ■ | ■ | +65/-70 | ■ | +65/-70 +65/-130* | ■ | ■ | ■ | |
| DOUBLE HUNG | (DH5460) | X/X Equal | 3-1/2" | 16-1/4" x 26-1/2" or 17-1/2" x 23-1/2" | 52-1/8" x 84" | ■ | ■ | ■ | ■ | ■ | +65/-70 | ■ | +65/-70 +65/-130* | ■ | ■ | ■ | |
| HORIZONTAL ROLLER | (HRS410) | XO / OX | 3-1/2" | 25-1/2" x 20-1/4" or 33-3/4" x 16-1/4" | 75" x 72" | ■ | ■ | ■ | ■ | ■ | +65/-70 | ■ | +65/-70 +65/-130* | ■ | ■ | ■ | |
| | | XOX 1/4-1/2-1/4 | 3-1/2" | 45-1/8" x 17" or 47-3/4" x 16-1/4" | 120" x 63" | ■ | ■ | ■ | ■ | ■ | +65/-70 | ■ | +65/-70 +65/-130* | ■ | ■ | ■ | |
| | | XOX 1/3-1/3-1/3 | 3-1/2" | 35-1/4" x 17-1/4" or 38" x 16-1/4" | 92" x 63" 120" x 63" | ■ | ■ | ■ | ■ | ■ | +65/-70 | ■ | +65/-70.7 +65/-130* | ■ | ■ | ■ | |
| CASEMENT | (CA5440) | X Standard Hinge | 3-1/2" | 17" x 20" | 36" x 75" | ■ | ■ | ■ | ■ | ■ | +50/-50 | ■ | +50/-50 +65/-114* | ■ | ■ | ■ | |
| | | X TrueHold Hinge | 3-1/2" | 17" x 20" | 40" x 84" | ■ | ■ | ■ | ■ | ■ | +65/-70 | ■ | +65/-70 +65/-130* | ■ | ■ | ■ | |
| AWNING | (AW5440) | X | 3-1/2" | 21-1/4" x 19-5/8" | 60" x 42" | ■ | ■ | ■ | ■ | ■ | +50/-50 | ■ | +50/-50 +65/-130* | ■ | ■ | ■ | |
| | | | | | 52-1/8" x 42" | | | | | | ■ | +65/-70 | ■ | +65/-70 +65/-130* | | | ■ |
| | | | | | 30" x 84" | | | | | | | | +65/-70 +65/-130* | ■ | | | |

+ Minimum/Maximum sizes may vary by shape. Refer to Quoting System for specific shape sizes.

* Maximum design pressure using comparative analysis on smaller sizes.



EnergyVue Vinyl Non-Impact Windows and Doors

PRODUCT QUICK REFERENCE GUIDE

| PRODUCT STYLES AND SIZES | | | | | FRAME STYLES | | | | FRAME COLORS | TEST METHODS AND CERTIFICATIONS | | | | | | | |
|----------------------------------|---------------|---|---|--------------------------------------|--|-------------------|-----------|-----------|-------------------------------|---------------------------------|-------------------|-----------------------|-----------------------|---------------------------|--------------|---|---|
| PRODUCT STYLE | CONFIGURATION | NOMINAL FRAME DEPTH | MINIMUM SIZE (ACTUAL DLO FRAME SIZE) | MAXIMUM SIZE (ACTUAL DLO FRAME SIZE) | 5/8" FLANGE | INTEGRAL NAIL FIN | J-CHANNEL | EQUAL LEG | WHITE, BEIGE BRONZE, BLACK | AAMA A440 | | TAS 201 / 202 / 203 | | FLORIDA PRODUCT APPROVAL | ENERGY STAR® | | |
| | | | | | | | | | | DESIGN PRESSURE* | KEY CERTIFICATION | DESIGN PRESSURE* | MIAMI-DADE NOA | | | | |
| PICTURE WINDOW / ARCHITECTURAL + | (PW/AR5420) | O | 3-1/2" | 10" x 16" | 96" x 63" | ■ | ■ | ■ | ■ | ■ | +50/-50 | ■ | | ■ | ■ | | |
| | | | | | 120" x 60" | | | | | | +70/-70 | ■ | | | | | |
| | | | | | Up to 50 sq. ft. | | | | | | | +70/-70 +80/-98.2* | | | | ■ | |
| | (PW/AR5440) | O | 3-1/2" | 12-1/2" x 18" | 96" x 63" | ■ | ■ | ■ | ■ | ■ | ■ | +50/-50 | ■ | | ■ | ■ | |
| | | | | | 120" x 60" | | | | | | | +70/-70 | ■ | | | | |
| | | | | | Up to 50 sq. ft. | | | | | | | | +70/-70 +80/-98.2* | | | | ■ |
| SLIDING GLASS DOOR | (SGD5470) | By-Pass or Pocket and 90° or 135° Corners | 2-track 5-7/8" 3-track 8-1/4" 4-track 10-5/8" | 22-15/16" x 27-3/4" panel | 4'0" x 8'0" panel | | | | | ■ | ■ | +80/-80 | ■ | +80/-80 +169.4/-169.4* | ■ | ■ | ■ |
| | | | | | 5'0" x 8'0" panel | | | | | | | +60/-60 | ■ | +60/-60 +74.1/-74.1* | ■ | | |
| | | | | | 4'0" x 10'0" panel | | | | | | | +60/-65 | ■ | +60/-65 +120/-130* | ■ | | |
| | (SGD5470NS) | By-Pass or Pocket and 90° Corners | 2-track 5-7/8" 3-track 8-1/4" 4-track 10-5/8" | 21-3/8" x 30" panel | 4'0" x 10'0" panel or 5'0" x 8'0" panel | | | | | ■ | ■ | +80/-85* | ■ | +80/-85* | ■ | ■ | ■ |
| | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | |
| FRENCH DOOR | (FDS455) | X | 4-9/16" | 20" x 74" | 38-3/4" x 96" | | | | | ■ | +70/-70 | ■ | +70/-70 | ■ | ■ | | |
| | | XX | 4-9/16" | 36" x 74" | 76" x 96" | | | | | ■ | +70/-70 | ■ | +70/-70 | ■ | ■ | | |
| | | O | 4-9/16" | 12" x 20" or 20" x 12" | 40" x 111" or 111" x 40" | | | | | ■ | +70/-70 | ■ | +70/-70 | ■ | ■ | | |

+ Minimum/Maximum sizes may vary by shape. Refer to Quoting System for specific shape sizes.
 * Maximum design pressure using comparative analysis on smaller sizes.